

1000 SRK

The Compact One



APPLICATION

ADVANTAGES

<p>In general</p>	<ul style="list-style-type: none"> ✓ Fast, gentle, and efficient ✓ Both climate friendly and health friendly ✓ Autonomous, mobile, can easily be hauled into a vehicle
<p>Parts cleaning</p>	<ul style="list-style-type: none"> ✓ Cleaning from precision parts up to 10 ton motor ✓ With or without cleaner, gentle on fragile surfaces ✓ Low water consumption
<p>Machine cleaning</p>	<ul style="list-style-type: none"> ✓ Using the own emulsion ✓ Ideal for areas which are difficult to access or fragile ✓ Reduction of stillstand times
<p>Cleaning at and under vehicles</p>	<ul style="list-style-type: none"> ✓ Cleaning of all mechanical parts directly at the vehicle ✓ Significantly cheaper than A1-brake cleaners ✓ Complies with rules of German trade associations
<p>Application examples</p>	<ul style="list-style-type: none"> ✓ Cleaning of tooling machines ✓ Oil filters, air filters, radiators, heat exchangers.... ✓ Ideal for service companies and technicians - easy to transport

Technical Data 1000 SRK

- Variants 1000 SRK-EA, 1000 SRK-AS and combination 1000 SRK-AS-EA
- EA: Uses direct external water supply
- AS: Enables the suction of liquids from a separate tank
- Small wheels at the handle allow for particularly easy loading and transportation



Technical Data	1000 SRK-AS	1000 SRK-EA
Working pressure	~ 3.0 - 7.5 bar	~ 3.0 - 7.5 bar + pre-pressure Heating capacity is reduced for total pressures (pre-pressure + pump) above 8 bar.
Working temperature	~ 95°C in 60 seconds	~ 95°C in 60 seconds
Spray-/water volume	~ 1.1 - 1.8 liters / min.	~ 1.1 - 2.4 liters / min.
Type of current	3P-N-PE/400V/50Hz/16A	3P-N-PE / 400V / 50Hz / 16A
Power consumption	10.1 KW	10.1 KW
Water supply	Suction from separate tank	External water supply with pre-pressure of 2 - 6 bar
Dimensions	92 x 48 x 45 cm	92 x 48 x 45 cm
Weight (empty)	~ 55 kg	~ 55 kg
Noise level	< 70 dBA	< 70 dBA
Pressure control	Stepless, on the unit	Stepless, on the unit
Temperature control	Option 1000 ET	Option 1000 ET
External suction	Standard	Only with AS-EA
Filter	25 µm	Only with AS-EA
Dosage pump cleaner	Not available	Option DE-DP
Connector cable	7.5 meters	7.5 meters
Hoses	Suction hose 5 meters Spray hose 5 meters	Suction hose only with AS-EA Spray hose 5 meters
Chassis custom colour	Option 1000 WF	Option 1000 WF

Subject to technical modifications. As of August 1, 2019.